



深圳德彩光电有限公司
Shenzhen Dicolor Optoelectronics Co.,Ltd

LED模组规格书

LED MODULE SPECIFICATION

编号 (NO.):	DI-P25Y
类型 (Type):	Outdoor LED Module
间距 (Pitch):	25 mm
驱动 (Driving):	Static Duty
版本 (Version):	1.0



请避免重物挤压灯面!



小心静电损坏 LED!



非专业人员请勿维修!

地址:深圳市宝安区福永镇福海大道福海科技工业园 B3区2栋4楼

Address:Floor 4,Seat 2,B3 District,FuHai Technology Industry Park,Fuyong Town,Shenzhen,China

电话(Tel):0086-755-29604770/29604771/29604749

传真(Fax):0086-755-29604042

网址(Web):Http//www.dicolor.cn

邮编(Post code):518103




深圳德彩光电有限公司

Shenzhen Dicolor Optoelectronics Co.,Ltd


DI-P25Y

户外模组 (OUTDOOR MODULE)

单位 / Unit : mm



FRONT VIEW




Pin Assignment (Data JP1/JP2 - F.C.16)


Pin NO.	Function	Pin NO.	Function
1	Y0	2	GND
3	GND	4	GND
5	Y1	6	GND
7	GND	8	GND
9	CLK	10	GND
11	LAT	12	GND
13	OE	14	GND
15	GND	16	GND

Pin Assignment (Power JP3 - CH5)

Pin NO.	Function
1	VDD
2	VDD
3	GND
4	GND
5	



BACK VIEW



SIDE VIEW



深圳德彩光电有限公司

Shenzhen Dicolor Optoelectronics Co.,Ltd

DI-P25Y

户外模组 (OUTDOOR MODULE)

主要技术指标


MAIN SPECIFICATIONS

(温度条件 Ta = 25°C)

项目 (ITEM)	参数 DESCRIPTION
像素间距 (Pixel Pitch)	Pitch 25 mm
显示分辨率 (Display resolution)	8 x 8 Dots
像素基色 (Pixel configuration)	3W
物理密度 (Physical density)	1600 (pixels / m ²)
驱动方式 (Driving Method)	Static Duty
外形尺寸 (Panel size)	200*200mm
灰度等级 (Gray scale)	
显示亮度 (Brightness)	6000 ± 10% Nit
模组视角 (Viewing angle)	H : 35° / V : 30°
最佳视距 (Option distance)	> 30 M
LED封装 (LED Encapsulation)	DIP 510
LED波长 (LED Wavelength)	
工作电压 (Working Voltage)	DC 12 V
使用功耗 (Working Consumption)	15W
使用寿命 (Life Time)	100,000 Hours
环境温度 (Environment Temperature)	-20°C ~ 60°C
外壳材质 (Material of Module Outside Frame)	PC

数据传输原理图

Drive Data Register Direction



FRONT VIEW (LAMP VIEW)