



深圳德彩光电有限公司

Shenzhen Dicolor Optoelectronics Co.,Ltd

# LED模组规格书

## LED MODULE SPECIFICATION

编号 ( NO. ):	DI-P5F1
类型 ( Type ):	Indoor LED Module
间距 ( Pitch ):	5.0 mm
驱动 ( Driving ):	1/8 Duty
版本 ( Version ):	1.0



请避免重物挤压灯面!



小心静电损坏LED!



非专业人员请勿维修!

地址:深圳市宝安区福永镇福海大道福海科技工业园B3区2栋4楼

Address:Floor 4,Seat 2,B3 District,FuHai Technology Industry Park,Fuyong Town,Shenzhen,China

电话(Tel):0086-755-29604770/29604771/29604749

传真(Fax):0086-755-29604042

网址(Web):Http//www.dicolor.cn

邮编(Post code):518103




# 深圳德彩光电有限公司

Shenzhen Dicolor Optoelectronics Co.,Ltd



DI-P5F1

户内模组 ( INDOOR MODULE )


单位 / Unit : mm



FRONT VIEW



BACK VIEW



SIDE VIEW

Pin Assignment (Data J1/J2 - F.C.16)

Pin NO.	Function	Pin NO.	Function
1	R0	2	G0
3	B0	4	GND
5	R1	6	G1
7	B1	8	GND
9	A	10	B
11	C	12	GND
13	CLR	14	LAT
15	OE	16	GND

Pin Assignment (Power J3 - CH5)

Pin NO.	Function
1	VDD
2	VDD
3	VCC
4	GND
5	GND



# 深圳德彩光电有限公司

Shenzhen Dicolor Optoelectronics Co.,Ltd

DI-P5F1

户内模组 ( INDOOR MODULE )

主要技术指标


MAIN SPECIFICATIONS

(温度条件 Ta = 25°C)

项目 (ITEM)	参数 DESCRIPTION
像素间距 (Pixel Pitch)	Pitch 5 mm
显示分辨率 (Display resolution)	32 x 16 Dots
像素基色 (Pixel configuration)	三合一 3(RGB) IN 1
物理密度 (Physical density)	40000 ( pixels / m <sup>2</sup> )
驱动方式 (Driving Method)	1/8 Duty
外形尺寸 (Panel size)	159.6x79.6mm
灰度等级 (Gray scale)	256 greys for each colour (16,7 77,216 grade) 每种颜色256级;共16,777,216级
显示亮度 (Brightness)	1500 ± 10% Nit
模组视角 (Viewing angle)	H:160° / V:120°
最佳视距 (Option distance)	> 6 M
LED封装 (LED Encapsulation)	SMD3528
LED波长 (LED Wavelength)	R:620~635nm G:515~530nm B:460~475nm
工作电压 (Working Voltage)	DC 5 V
使用功耗 (Working Consumption)	38 W
使用寿命 (Life Time)	100,000 Hours
环境温度 (Environment Temperature)	-20° C ~ 60° C

数据传输原理图

Drive Data Register Direction



FRONT VIEW (LAMP VIEW)